

Sentry Enhancer H2O

Description	Sentry Enhancer H2O is a water based sealer with enhancement that brings out natural color while adding minimal sheen. It provides resistance to moisture, dirt, food and beverage spills.
Surface	For most porous surfaces, Natural and Artificial Stone, Concrete, Masonry Products and Wood Decks and Outdoor Furniture. Not to be used over currently painted or sealed surfaces.
Solution	Repels Moisture, Stains, Ice, Mold and Dirt.
Characteristics	Color: Slightly milky white Odor: none to slight Flash Point: N/A VOC: 0 g/L Weight per gallon: 8 lb./gallon Breathable: Yes
Coverage	200 to 600 SqFt. /gal Coverage will vary depending on the porosity of substrate.
Surface Preparation	Surface must be clean, dry and in sound condition. To remove all oil, dust, grease, dirt, loose material including the removal of all existing silicon sealers. Use Sentry Step#1 Cleaner for Unpainted Surfaces then rinse with clean fresh water and dry completely.
Application Instruction	<p>Test Area Due to a wide range of materials and blends of materials always test sample for compatibility.</p> <p>Application</p> <ul style="list-style-type: none"> • Shake container thoroughly before & during application • Apply a flood coat on the surface with the sealer using a pump sprayer, or pour onto surface. • Back roll in the sealer with a 3/8" nap roller or micro fiber mop several times back and forth and up and down applying down pressure to force sealer into the surface. Do not leave any puddles as they will turn white. • After 10-15 minutes, apply an additional coat to ensure full saturation. (More than 2 coats may be necessary on very porous surfaces, keep applying every 10-15 minutes until the surface you are sealing will not absorb any more sealer). • Additional coats MUST be applied within the 10-15 minute time so it goes on wet-on- wet • Air and surface temperatures should be between 45F and 105 RH 90% or less • DO NOT REDUCE • Protect against rain for 5 hours.
Dry Time	Drying time is temperature and humidity dependent. Touch: 1-2 hour. Through: 3-5 hours light foot traffic Full Cure: 3-5 days
Storage	Do not freeze or boil. Use within 2 years of date of purchase.
Clean Up	Clean tools and flush equipment with warm, soapy water.
Maintenance	Broom sweep or wash with water with pistol grip, do not use power washers as this will reduce the longevity of the sealer.
Caution	In the event of contact with skin, wash skin thoroughly with soap and water. In case of contact with eyes, immediately flush eyes with water for 15 minutes after contact and get medical attention. If accidentally swallowed, rinse mouth thoroughly and obtain immediate medical attention. (In enclosed areas, make sure to have an observer watching the applicator for any signs of physical distress.)

Warranty	Limited 2 Year Sentry Molecular Coatings Inc. guarantees Sentry Enhancer H2O to be defect free from date of purchase for 2 years and any material that is proven to be defective will be replaced in a like quantity by the manufacturer with proof of purchase receipt, and provided it has been applied according to the instructions on container and data sheet along with other related guidelines posted at SentryMolecularCoatings.com. This warranty only extends to the owner of the property upon which the product is applied and is non-transferable. Seller will replace product 100% of full value for the first 1 year then prorated for the remaining 1 year. Warranty does not cover wear and tear only manufactures defects. Any warranty claim must be made in writing and sent to Seller with supporting materials and access to the property for inspection and testing as requested by Seller. Seller will thereafter provide replacement product for product found to be defective. This warranty is given in lieu of all other warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose. The remedy stated herein is an exclusive remedy and Seller shall not be responsible for any other damages, including labor or any incidental, consequential, special or punitive damages, whether based on breach of express or implied warranty, negligence, strict liability or other legal theory.
-----------------	---